



TRANSMISSION

FULL SYNTHETIC MULTI-VEHICLE CONTINUOUSLY VARIABLE TRANSMISSION FLUID *PROFESSIONAL-SERIES*

PT#3100	RLO#1085823	UNIT 32 oz.	CASE SIZE 6/cs	PALLET UNITS 1008
---------	-------------	-------------	----------------	-------------------

PT#3300	RLO#1085778	UNIT 1 Gal.	CASE SIZE 4/cs	PALLET UNITS 240
---------	-------------	-------------	----------------	------------------

Ensures proper performance an operation of continuously variable transmission.



- Meets performance requirements for nearly all vehicles with belt-type continuously variable transmissions
- Chain driven CVT & Step type transmissions
- High steel-on-steel friction to prevent belt slippage
- Low steel-on-paper friction to prevent torque converter clutch slippage
- Excellent oxidation resistance and thermal stability for long fluid life
- Protects against sludge and varnish formation
- Protects against wear, rust, and corrosion
- Excellent low-temperature properties for easier shifting in cold weather
- Good seal compatibility & good foam resistance
- Red Line Service Chemical Limited Lifetime Warranty Program coverage (if used every 30,000 miles)*

Specifically designed and formulated to meet performance requirements and specifications of most continuously variable transmissions.

Delivers proven performance

*See warranty information for complete details



Manufactured for **Red Line Synthetic Oil**
6100 Egret Court Benicia, CA 94510
707-745-6100

REDLINECHEMICALS.COM





TRANSMISSION



FULL SYNTHETIC MULTI-VEHICLE CONTINUOUSLY VARIABLE TRANSMISSION FLUID *PROFESSIONAL-SERIES*

PT#3100	RLO#1085823	UNIT 32 oz.	CASE SIZE 6/cs	PALLET UNITS 1008
PT#3300	RLO#1085778	UNIT 1 Gal.	CASE SIZE 4/cs	PALLET UNITS 240

RED LINE[®] MULTI-VEHICLE CVT FLUID is specifically designed and formulated to meet performance requirements and specifications of Continuously Variable Transmissions (CVT).

- Suitable for use in ALL CVT applications (As well as many step-type automatic transmission applications. Do not use where an ultra-low viscosity ATF is recommended)
- Optimized for excellent metal-metal friction performance
- Provides advanced wear protection, anti-shudder performance and oxidation stability
- Excellent low temperature fluidity for proper operation in cold weather conditions
- Protects against sludge and varnish build up
- Helps ensure proper performance and operation of CVT

RECOMMENDED SERVICE PROCEDURE:

- 1 For use in CVT Service Fill or Top Off applications. Consult vehicles owners manual for OEM recommended service intervals and fluid capacities.

DO NOT OVER FILL.



WARNING: This product can expose you to chemicals including 1-Naphthylamine (CASRN 134-32-7) which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.



Manufactured for **Red Line Synthetic Oil**
6100 Egret Court Benicia, CA 94510
707-745-6100

REDLINECHEMICALS.COM

